## Patent Claims

An integrated circuit arrangement which has: 1. an output circuit having at least one first output connection which can provide a data signal; at least one first data output connection, with the at least first output connection and the at least one data output connection having at least one first inductance connected between them.

10

15

- The integrated circuit arrangement as claimed in 2. claim 1, where the output circuit has a second output connection and a second data output connection, said second output connection and said second data output connection having at least one second inductance connected between them.
- The integrated circuit arrangement as claimed in 3. claim 2, where the first inductance is in a form such that it forms a first frequency filter having a 20 prescribed frequency band together with the first data output connection, and the second inductance is in a form such that it forms a second frequency filter having the prescribed frequency band together with the 25 second data output connection.
  - The integrated circuit arrangement as claimed in 4. claim 3, where the prescribed frequency band is in a range from 1 GHz to 100 GHz.

30

35

- The integrated circuit arrangement as claimed in 5. 1 to 4, which has a plurality of one of claims frequency filters coupled in series between the at least first output connection and the at least first data output connection.
- The integrated circuit arrangement as claimed in one of claims 2 to 5, where the output circuit is set

up such that a differential data signal can be provided at the first output connection and at the second output connection.

- The integrated circuit arrangement as claimed in claim 6, where the at least one first inductance is coupled to the at least one second inductance.
- The integrated circuit arrangement as claimed in 8. one of claims 1 to 7, where at least one of the 10 inductances is a monolithically integrated inductance.
- The integrated circuit arrangement as claimed in 9. one of claims 1 to 8, where the output circuit has a differential amplifier. 15
  - 10. The integrated circuit arrangement as claimed in one of claims 1 to 8, where the output circuit has a multiplexer.